



Properties

| | |
|-------------------|----------------|
| Base Construction | Steel |
| Lens | Fabric/Acrylic |
| Application | Flush Mount |
| Location | Damp |
| CRI | 80 |
| Life Hours | 50,000 |
| Light Source | Integrated LED |

Standard Selection

| | |
|---------|--------------------------------------|
| Voltage | 120V-277V (non dimming) |
| Finish | Brushed Nickel Trim With Fabric Lens |
| CCT | 3000K |

Finish Options

- Brushed Nickel Trim With Fabric Lens

Fabric Finish

- Grey Linen

CCT Options

| | |
|-----|-------|
| CCT | 3000K |
|-----|-------|

Options

| Size | Dimensions | Wattage | Voltage | Lumens |
|--------|----------------|----------|------------------------------|----------------|
| RFO-17 | D:17.5" H:5.5" | 15/24 | DV (120V-277V (non dimming)) | 1950/3120 |
| RFO-20 | D:20.8" H:6.1" | 15/25/35 | DV (120V-277V (non dimming)) | 1950/3250/4550 |

Options

- EMG - Emergency
- OS - Occupancy Sensor
- OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us!

info@asllighting.com