



**Properties**

|                          |                   |
|--------------------------|-------------------|
| <b>Base Construction</b> | Cold-rolled Steel |
| <b>Lens</b>              | Acrylic           |
| <b>Application</b>       | Flush Mount       |
| <b>Location</b>          | Damp              |
| <b>CRI</b>               | 80                |
| <b>Life Hours</b>        | 50,000            |
| <b>Light Source</b>      | Integrated LED    |

**Standard Selection**

|                |                        |
|----------------|------------------------|
| <b>Voltage</b> | 120V-277V 0-10 dimming |
| <b>Finish</b>  | White                  |
| <b>CCT</b>     | 3000K                  |

**Finish Options**

White

**CCT Options**

|            |                               |
|------------|-------------------------------|
| <b>CCT</b> | 2700K/3000K/3500k/4000K/5000K |
|------------|-------------------------------|

**Options**

| Size     | Dimensions     | Wattage  | Voltage   | Lumens         |
|----------|----------------|----------|---|----------------|
| RFOBA-16 | D:16.1" H:3.6" | 15/24    | ND (120V (non dimming)) / TD (120V Triac dimming)<br>DVD (120V-277V 0-10 dimming) | 1950/3120      |
| RFOBA-21 | D:20.8" H:3.6" | 15/25/35 | DVD (120V-277V 0-10 dimming) / ND (120V (non dimming))<br>TD (120V Triac dimming) | 1950/3250/4550 |

**Options**

- EMG - Emergency
- OS - Occupancy Sensor
- OSCD - Occupancy Sensor Step Dimming

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)