




### Properties

|                   |                   |
|-------------------|-------------------|
| Base Construction | Cold-rolled Steel |
| Lens              | Acrylic           |
| Application       | Flush Mount       |
| Location          | Damp              |
| CRI               | 80                |
| Life Hours        | 50,000            |
| Light Source      | Integrated LED    |

### Standard Selection

|         |                         |
|---------|-------------------------|
| Voltage | 120V-277V (non dimming) |
| Finish  | ORB                     |
| CCT     | 3000K                   |

### Finish Options

|  |  |
|--|--|
|  Black          |  Bronze     |
|  Brushed Nickel |  Gold/Brass |
|  ORB          |  White    |

### CCT Options

|     |       |
|-----|-------|
| CCT | 3000K |
|-----|-------|

### Options

| Size    | Dimensions     | Wattage | Voltage                      | Lumens |
|---------|----------------|---------|------------------------------|--------|
| RFOO-12 | D:11.8" H:2.8" | 20      | DV (120V-277V (non dimming)) | 2600   |
| RFOO-16 | D:15.8" H:2.8" | 35      | DV (120V-277V (non dimming)) | 4550   |
| RFOO-20 | D:19.7" H:2.8" | 44      | DV (120V-277V (non dimming)) | 5720   |

Not seeing what you're looking for?  
Contact us!  
[info@asllighting.com](mailto:info@asllighting.com)