



**Properties**

<b>Base Construction</b>	Steel
<b>Lens</b>	Acrylic
<b>Application</b>	Over Bed
<b>Location</b>	Damp
<b>CRI</b>	80
<b>Life Hours</b>	50,000
<b>Light Source</b>	Integrated LED
<b>Light Direction</b>	UP & DOWN WITH 4WAY PULL CHAIN

**Standard Selection**

<b>Voltage</b>	120V-277V 0-10 dimming
<b>Finish</b>	Brushed Nickel
<b>CCT</b>	3500k

**Finish Options**

- Black
- Bronze
- Brushed Nickel
- Gold/Brass
- ORB
- White

**CCT Options**

<b>CCT</b>	2700K/3000K/3500k/4000K
------------	-------------------------



**Options**

Size	Dimensions	Wattage	Voltage	Lumens
RFSB-24	H:6" L:24" E:4"	20/24/30	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600/3120/3900
RFSB-36	H:6" L:36" E:4"	20/30/40	DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) ND (120V (non dimming)) / TD (120V Triac dimming)	2600/3900/5200
RFSB-48	H:6" L:48" E:4"	30/46/55	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	3900/5980/7150

**Options**

- EMG - Emergency
- OS - Occupancy Sensor
- OSCD - Occupancy Sensor Step Dimming

**Not seeing what you're looking for?**

Contact us!  
[info@asllighting.com](mailto:info@asllighting.com)