



**Properties**

<b>Base Construction</b>	Cold-rolled Steel
<b>Lens</b>	Acrylic
<b>Application</b>	Flush Mount
<b>Location</b>	Damp
<b>CRI</b>	80
<b>Life Hours</b>	50,000
<b>Light Source</b>	Integrated LED

**Standard Selection**

<b>Voltage</b>	120V Triac dimming
<b>Finish</b>	Brushed Nickel
<b>CCT</b>	3000K

**Finish Options**

- Black
- Bronze
- Brushed Nickel
- Gold/Brass
- ORB
- White

**CCT Options**

<b>CCT</b>	2700K/3000K/3500k/4000K/5000K
------------	-------------------------------

**Options**

Size	Dimensions	Wattage	Voltage	Lumens
RFUB-10	D:10.5" H:2.6"	10/17	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/2210
RFUB-15	D:15" H:2.6"	10/15/23	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/1950/2990
RFUB-19	D:19" H:2.6"	15/25/35	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/3250/4550

**Options**

- EMG - Emergency
- OS - Occupancy Sensor
- OSCD - Occupancy Sensor Step Dimming

**Not seeing what you're looking for?**

Contact us!  
[info@asllighting.com](mailto:info@asllighting.com)