



Properties

Base Construction	Cold-rolled Steel
Lens	Acrylic
Application	Flush Mount
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED

Standard Selection

Voltage	120V (non dimming)
Finish	Gold/Brass
CCT	3000K

Finish Options

- Black
- Brushed Nickel
- ORB
- Bronze
- Gold/Brass
- White

CCT Options

CCT	3000K/4000K/3CCT
-----	------------------

Options

Size	Dimensions	Wattage	Voltage	Lumens
RFUBB-14	D:14.6" H:3"	10/12/15/20/25	ND (120V (non dimming))	1300/1560/1950/2600/3250
RFUBB-16	D:16" H:3"	10/18/25	ND (120V (non dimming))	1300/2340/3250
RFUBB-18	D:17.8" H:3"	15/20/25	ND (120V (non dimming))	1950/2600/3250
RFUBB-21	D:20.5" H:3"	15/20/25/32	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/2600/3250/4160

Not seeing what you're looking for?

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)