



### Properties

<b>Base Construction</b>	Aluminum
<b>Lens</b>	Frosted Glass
<b>Application</b>	Pendant
<b>Location</b>	Damp
<b>CRI</b>	80
<b>Life Hours</b>	50,000
<b>Light Source</b>	Integrated LED

### Standard Selection

<b>Voltage</b>	120V-277V (non dimming)
<b>Finish</b>	Brushed Nickel
<b>CCT</b>	3000K

### Finish Options

- Black
- Bronze
- Brushed Nickel
- Gold/Brass
- ORB
- White

### CCT Options

<b>CCT</b>	2700K/3000K/3500k/4000K/5000K
------------	-------------------------------

### Options

Size	Dimensions	Wattage	Voltage	Lumens
RFUBC-15	D:15" H:2.6" MH:72"	15	DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) ND (120V (non dimming)) / TD (120V Triac dimming)	1950
RFUBC-19	D:19" H:2.6" MH:72"	19	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2470

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)