



Properties

| | |
|--------------------------|-------------------|
| Base Construction | Cold-rolled Steel |
| Lens | Linen |
| Application | Semi-flush |
| Location | Damp |
| CRI | 80 |
| Life Hours | 50,000 |
| Light Source | Integrated LED |

Standard Selection

| | |
|----------------|-------------------------|
| Voltage | 120V-277V (non dimming) |
| Finish | WHITE LINEN |
| CCT | 3000K |

Finish Options

WHITE LINEN

CCT Options

| | |
|------------|-------------------------------|
| CCT | 2700K/3000K/3500k/4000K/5000K |
|------------|-------------------------------|

Options

| Size | Dimensions | Wattage | Voltage | Lumens |
|---------|---------------------|---------|--|--------|
| RFUC-12 | D:11.7" H:5" MH:12" | 18 | ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 2340 |
| RFUC-15 | D:14.5" H:5" MH:12" | 24 | ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 3120 |
| RFUC-18 | D:17.7" H:5" MH:12" | 35 | ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 4550 |

Not seeing what you're looking for?

Contact us!

info@asllighting.com