



Properties

Base Construction	Cold-rolled Steel
Lens	Acrylic
Application	Flush Mount
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED

Standard Selection

Voltage	120V-277V (non dimming)
Finish	Brushed Nickel Trim With Fabric Lens
CCT	3000K

Finish Options

- Brushed Nickel Trim With Fabric Lens

Fabric Finish

- White Linen

CCT Options

CCT	2700K/3000K/3500k/4000K/5000K
------------	-------------------------------

Options

Size	Dimensions	Wattage	Voltage	Lumens
RFUY-12	D:12" H:5"	10/18/25	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/2340/3250
RFUY-16	D:15.4" H:5.2"	10/15/24/30	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/1950/3120/3900
RFUY-18	D:18.5" H:5.7"	15/20/25/35	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/2600/3250/4550

Options

- EMG - Emergency
- OS - Occupancy Sensor
- OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us!

info@asllighting.com