



Properties

|                   |                   |
|-------------------|-------------------|
| Base Construction | Cold-rolled Steel |
| Lens              | Acrylic           |
| Application       | Flush Mount       |
| Location          | Damp              |
| CRI               | 80                |
| Life Hours        | 50,000            |
| Light Source      | Integrated LED    |

Standard Selection

|         |                                      |
|---------|--------------------------------------|
| Voltage | 120V-277V (non dimming)              |
| Finish  | Brushed Nickel Trim With Fabric Lens |
| CCT     | 3000K                                |

Finish Options

 Brushed Nickel Trim With Fabric Lens

Fabric Finish

 White Linen

CCT Options

|     |                               |
|-----|-------------------------------|
| CCT | 2700K/3000K/3500k/4000K/5000K |
|-----|-------------------------------|

Options

| Size    | Dimensions     | Wattage     | Voltage  | Lumens              |
|---------|----------------|-------------|--|---------------------|
| RFUY-12 | D:12" H:5"     | 10/18/25    | ND (120V (non dimming)) / TD (120V Triac dimming)<br>DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1300/2340/3250      |
| RFUY-16 | D:15.4" H:5.2" | 10/15/24/30 | ND (120V (non dimming)) / TD (120V Triac dimming)<br>DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1300/1950/3120/3900 |
| RFUY-18 | D:18.5" H:5.7" | 15/20/25/35 | ND (120V (non dimming)) / TD (120V Triac dimming)<br>DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1950/2600/3250/4550 |

Options

- EMG - Emergency
- OS - Occupancy Sensor
- OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)