


Properties

Base Construction	Steel
Lens	Acrylic
Application	Sconce
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED
Light Direction	UP AND DOWN

Standard Selection

Voltage	120V (non dimming)
Finish	Brushed Nickel
CCT	3000K

Finish Options

<input type="checkbox"/> Black	<input type="checkbox"/> Bronze
<input type="checkbox"/> Brushed Nickel	<input type="checkbox"/> Gold/Brass
<input type="checkbox"/> ORB	<input type="checkbox"/> White

CCT Options

CCT	2700K/3000K/3500k/4000K/5000K
------------	-------------------------------


Options

Size	Dimensions	Wattage	Voltage	Lumens
TLBC-8	H:12" W:6" E:4"	10/15	DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) ND (120V (non dimming)) / TD (120V Triac dimming)	1300/1950
TLBC-12	H:8" W:6" E:4"	10/15	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/1950
TLBC-7	H:7.5" W:7.5" E:3.75"	10	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300
TLBC-12x8	H:8" W:12" E:4"	10/15/20	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/1950/2600

Options

- EMG – Emergency
- OS - Occupancy Sensor
- OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us!

info@asllighting.com