


Properties

| | |
|--------------------------|----------------|
| Base Construction | Steel |
| Lens | Acrylic |
| Application | Sconce |
| Location | Damp |
| CRI | 80 |
| Life Hours | 50,000 |
| Light Source | Integrated LED |
| Light Direction | UP AND DOWN |

Standard Selection

| | |
|----------------|--------------------|
| Voltage | 120V (non dimming) |
| Finish | Brushed Nickel |
| CCT | 3000K |

Finish Options

- Black
- Bronze
- Brushed Nickel
- Gold/Brass
- ORB
- White

CCT Options

| | |
|------------|-------------------------------|
| CCT | 2700K/3000K/3500k/4000K/5000K |
|------------|-------------------------------|


Options

| Size | Dimensions | Wattage | Voltage | Lumens |
|-----------|-----------------------|----------|--|----------------|
| TLBC-8 | H:12" W:6" E:4" | 10/15 | ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1300/1950 |
| TLBC-12 | H:8" W:6" E:4" | 10/15 | ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1300/1950 |
| TLBC-7 | H:7.5" W:7.5" E:3.75" | 10 | ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1300 |
| TLBC-12x8 | H:8" W:12" E:4" | 10/15/20 | ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1300/1950/2600 |

Options

- EMG – Emergency
- OS - Occupancy Sensor
- OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us!

info@asllighting.com