



### Properties

<b>Base Construction</b>	Cold-rolled Steel
<b>Lens</b>	Acrylic
<b>Application</b>	Vanity
<b>Location</b>	Damp
<b>CRI</b>	80
<b>Life Hours</b>	50,000
<b>Light Source</b>	Integrated LED

### Standard Selection

<b>Voltage</b>	120V-277V (non dimming)
<b>Finish</b>	Brushed Nickel
<b>CCT</b>	3CCT - 3000K / 3500K / 4000K

### Finish Options

- Black
- Bronze
- Brushed Nickel
- Gold/Brass
- ORB
- White

### CCT Options

<b>CCT</b>	3CCT
------------	------

### Options

Size	Dimensions	Wattage	Voltage	Lumens
VBEA-25	L:25.5" H:4.4" E:3.8"	10/17/20	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/2210/2600
VBEA-37	L:37.3" H:4.4" E:3.8"	15/24/25	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/3120/3250
VBEA-49	L:49.1" H:4.4" E:3.8"	20/25/36	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600/3250/4680

### Options

- BBX-Backbox W/ 3/4" Conduit hole
- EMG - Emergency

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)