







## **Properties**

Base Construction Cold-rolled			
Lens	Acrylic		
Application	Vanity		
Location	Damp		
CRI	80		
Life Hours	50,000		
Light Source	Integrated LED		

## **Standard Selection**

Voltage	120V-277V (non dimming) Brushed Nickel		
Finish			
сст	3000K		
Finish Options			
Black	■ Bronze		

Brushed Nickel Gold/Brass

**CCT Options** 

ORB

2700K/3000K/3500k/4000K/5000K CCT

White

Size	Dimensions	Wattage	Voltage	L	umens
VBH-22	L:22" H:4.8" E:3.8"	11	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)		1430
VBH-34	L:34" H:4.8" E:3.8"	18	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)		2340
VBH-46	L:46" H:4.8" E:3.8"	23	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)		2990

Not seeing what you're looking for?

Contact us!

info@asllighting.com