





VBHE-46



Properties

Cold-rolled Steel	
Acrylic	
Vanity	
Damp	
80	
50,000	
Integrated LED	

Standard Selection

Voltage	120V-277V (non dimming)
Finish	Brushed Nickel
ССТ	3CCT - 3000K / 3500K / 4000K
Finish Options	
Black	Bronze

Brushed Nickel Gold/Brass

ORB White

CCT Options

CCT3CCT

Options				
Size	Dimensions	Wattage	Voltage	Lumens
VBHE-22	L:22" H:4.7" E:2.7"	10/17/20	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/2210/2600
VBHE-34	L:34" H:4.7" E:2.7"	15/23/25	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/2990/3250
VPUE 44	1.44" [].4 7" [].9 7"	20/25/25	ND (120V (non dimming)) / TD (120V Triac dimming)	2400/2250/4550

Not seeing what you're looking for?

2600/3250/4550

Contact us!

info@asllighting.com

L:46" H:4.7" E:2.7" 20/25/35

DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)