



Properties

| | |
|--------------------------|-------------------|
| Base Construction | Cold-rolled Steel |
| Lens | Acrylic |
| Application | Vanity |
| Location | Damp |
| CRI | 80 |
| Life Hours | 50,000 |
| Light Source | Integrated LED |

Standard Selection

| | |
|----------------|-------------------------|
| Voltage | 120V-277V (non dimming) |
| Finish | Brushed Nickel |
| CCT | 3000K |

Finish Options

- Black
- Bronze
- Brushed Nickel
- Gold/Brass
- ORB
- White

CCT Options

| | |
|------------|-------------------------------|
| CCT | 2700K/3000K/3500k/4000K/5000K |
|------------|-------------------------------|

Options

| Size | Dimensions | Wattage | Voltage | Lumens |
|---------|---------------------|----------|--|----------------|
| VBJG-24 | L:24" H:4.3" E:3.7" | 10/15/20 | ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1300/1950/2600 |
| VBJG-36 | L:36" H:4.3" E:3.7" | 15/22/25 | ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1950/2860/3250 |
| VBJG-48 | L:48" H:4.3" E:3.7" | 20/25/32 | ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 2600/3250/4160 |

Options

EMG - Emergency

Not seeing what you're looking for?

Contact us!

info@asllighting.com