



Properties

Base Construction	Cold-rolled Steel
Lens	Acrylic
Application	Vanity
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED

Standard Selection

Voltage	120V-277V (non dimming)
Finish	Brushed Nickel
CCT	3000K

Finish Options

- Black
- Bronze
- Brushed Nickel
- Gold/Brass
- ORB
- White

CCT Options

CCT	2700K/3000K/3500k/4000K/5000K
------------	-------------------------------

Options

Size	Dimensions	Wattage	Voltage	Lumens
VBJG-24	L:24" H:4.3" E:3.7"	10/15/20	DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) ND (120V (non dimming)) / TD (120V Triac dimming)	1300/1950/2600
VBJG-36	L:36" H:4.3" E:3.7"	15/22/25	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/2860/3250
VBJG-48	L:48" H:4.3" E:3.7"	20/25/32	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600/3250/4160

Options

EMG - Emergency

Not seeing what you're looking for?

Contact us!

info@asllighting.com