



Properties

Base Construction	Cold-rolled Steel
Lens	Acrylic
Application	Vanity
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED

Standard Selection

Voltage	120V-277V (non dimming)
Finish	ORB
CCT	3CCT - 3000K / 3500K / 4000K

Finish Options

- Black
- Bronze
- Brushed Nickel
- Gold/Brass
- ORB
- White

CCT Options

CCT	3CCT
------------	------

Options

Size	Dimensions	Wattage	Voltage	Lumens
VBJH-22	L:22" H:4.3" E:2.9"	23	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2990
VBJH-34	L:34" H:4.3" E:2.9"	35	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	4550
VBJH-46	L:46" H:4.3" E:2.9"	50	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	6500

Not seeing what you're looking for?

Contact us!

info@asllighting.com