



Properties

Base Construction	Cold-rolled Steel
Lens	Acrylic
Application	Vanity
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED

Standard Selection

Voltage	120V-277V (non dimming)
Finish	ORB
CCT	3CCT - 3000K / 3500K / 4000K

Finish Options

Black	Bronze
Brushed Nickel	Gold/Brass
ORB	White

CCT Options

CCT	3CCT
-----	------

Options

Size	Dimensions	Wattage	Voltage	Lumens
VBOMB-22	L:22" H:4.8" E:3.3"	17	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2210
VBOMB-34	L:34" H:4.8" E:3.3"	22	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2860
VBOMB-46	L:46" H:4.8" E:3.3"	34	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	4420

Not seeing what you're looking for?

Contact us!

info@asllighting.com