



### Properties

|                          |                |
|--------------------------|----------------|
| <b>Base Construction</b> | Steel          |
| <b>Lens</b>              | Acrylic        |
| <b>Application</b>       | Vanity         |
| <b>Location</b>          | Damp           |
| <b>CRI</b>               | 80             |
| <b>Life Hours</b>        | 50,000         |
| <b>Light Source</b>      | Integrated LED |

### Standard Selection

|                |                    |
|----------------|--------------------|
| <b>Voltage</b> | 120V (non dimming) |
| <b>Finish</b>  | Brushed Nickel     |
| <b>CCT</b>     | 3000K              |

### Finish Options

- Black
- Bronze
- Brushed Nickel
- Gold/Brass
- ORB
- White

### CCT Options

|            |                               |
|------------|-------------------------------|
| <b>CCT</b> | 2700K/3000K/3500k/4000K/5000K |
|------------|-------------------------------|

### Options

| Size   | Dimensions             | Wattage  | Voltage  | Lumens         |
|--------|------------------------|----------|--|----------------|
| VBW-22 | L:22" H:4.75" E:2.5"   | 15/20/25 | ND (120V (non dimming)) / TD (120V Triac dimming)<br>DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1950/2600/3250 |
| VBW-34 | L:34.5" H:4.75" E:2.5" | 20/25/30 | ND (120V (non dimming)) / TD (120V Triac dimming)<br>DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 2600/3250/3900 |
| VBW-46 | L:46" H:4.75" E:2.5"   | 20/30/40 | ND (120V (non dimming)) / TD (120V Triac dimming)<br>DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 2600/3900/5200 |

### Options

- BBX-Backbox W/ 3/4" Conduit hole
- EMG - Emergency
- OS - Occupancy Sensor
- OSCD - Occupancy Sensor Step Dimming

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)