VBX
Vanity

ADA Compliant

Properties

Base Construction	Steel
Lens	Acrylic
Application	Vanity
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED

Standard Selection

Voltage	120V (non dimming)
Finish	Brushed Nickel
CCT	3000K

Finish Options

- Black
- Bronze
- Brushed Nickel
- Gold/Brass
- ORB
- White

CCT Options

CCT	2700K/3000K/3500k/4000K/5000K

Options

Size	Dimensions	Wattage	Voltage	Lumens
VBX-25	L:25" H:4.8" E:3.9"	10/17/25	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/2210/3250
VBX-37	L:37" H:4.8" E:3.9"	15/23/30	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/2990/3900
VBX-49	L:49" H:4.8" E:3.9"	25/30/35/40	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	3250/3900/4550/5200

Options

EMG - Emergency

Not seeing what you're looking for?

Contact us!

info@asllighting.com

© Copyright © 2025 ASL Lighting Inc. All rights reserved.

asllighting.com