



Properties

| | |
|-------------------|-------------------|
| Base Construction | Die Cast Aluminum |
| Lens | Polycarbonate |
| Application | Sconce |
| Location | Wet |
| CRI | 80 |
| Life Hours | 50,000 |
| Light Source | Integrated LED |

Standard Selection

| | |
|---------|--------------------|
| Voltage | 120V (non dimming) |
| Finish | Black |
| CCT | 3000K |

Finish Options

- Black
- Brushed Nickel
- Gold/Brass
- ORB
- White

CCT Options

| | |
|-----|-------------------------------|
| CCT | 2700K/3000K/3500k/4000K/5000K |
|-----|-------------------------------|

Options

| Size | Dimensions | Wattage | Voltage | Lumens |
|--------|-------------------------|----------|--|----------------|
| VWS-13 | H:12.5" W:12.5" E:3.93" | 12/17/25 | ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1560/2210/3250 |

Options

- EMG - Emergency
- OS - Occupancy Sensor
- OSCD - Occupancy Sensor Step Dimming
- OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us!

info@asllighting.com