



Properties

| | |
|--------------------------|-------------------|
| Base Construction | Die Cast Aluminum |
| Lens | Polycarbonate |
| Application | Sconce |
| Location | Wet |
| CRI | 80 |
| Life Hours | 50,000 |
| Light Source | Integrated LED |

Standard Selection

| | |
|----------------|--------------------|
| Voltage | 120V (non dimming) |
| Finish | Black |
| CCT | 3000K |

Finish Options

- Black
- Brushed Nickel
- Gold/Brass
- ORB
- White

CCT Options

| | |
|------------|-------------------------------|
| CCT | 2700K/3000K/3500k/4000K/5000K |
|------------|-------------------------------|

Options

| Size | Dimensions | Wattage | Voltage | Lumens |
|--------|----------------|-------------|--|---------------------|
| WCR-13 | D:12.8" E:3.8" | 10/15/20/25 | ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1300/1950/2600/3250 |

Options

- EMG - Emergency
- OS - Occupancy Sensor
- OSCD - Occupancy Sensor Step Dimming
- OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us!

info@asllighting.com