



Properties

|                   |                   |
|-------------------|-------------------|
| Base Construction | Cold-rolled Steel |
| Lens              | Acrylic           |
| Application       | Flush Mount       |
| Location          | Damp              |
| CRI               | 80                |
| Life Hours        | 50,000            |
| Light Source      | Integrated LED    |

Standard Selection

|         |                         |
|---------|-------------------------|
| Voltage | 120V-277V (non dimming) |
| Finish  | Grey/Gold               |
| CCT     | 4000K                   |

Finish Options

- Black
- Brushed Nickel
- ORB
- Grey/Gold
- Bronze
- Gold/Brass
- White

CCT Options

|     |                         |
|-----|-------------------------|
| CCT | 2700K/3500k/4000K/5000K |
|-----|-------------------------|

Options

| Size    | Dimensions   | Wattage | Voltage  | Lumens    |
|---------|--------------|---------|--|-----------|
| WFBA-16 | D:16.5" H:6" | 17/25   | ND (120V (non dimming)) / TD (120V Triac dimming)<br>DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 2210/3250 |

Options

- OS - Occupancy Sensor
- OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)