



Properties

| | |
|--------------------------|-------------------|
| Base Construction | Cold-rolled Steel |
| Lens | Acrylic |
| Application | Flush Mount |
| Location | Damp |
| CRI | 80 |
| Life Hours | 50,000 |
| Light Source | Integrated LED |

Standard Selection

| | |
|----------------|-------------------------|
| Voltage | 120V-277V (non dimming) |
| Finish | Brushed Nickel |
| CCT | 3000K |

Finish Options

- Black
- Bronze
- Brushed Nickel
- Gold/Brass
- ORB
- White

CCT Options

| | |
|------------|-------------------------------|
| CCT | 2700K/3000K/3500k/4000K/5000K |
|------------|-------------------------------|

Options

| Size | Dimensions | Wattage | Voltage | Lumens |
|--------|----------------|----------|--|----------------|
| WFR-14 | D:14.8" H:4" | 15/24 | ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1950/3120 |
| WFR-17 | D:16.5" H:4.5" | 15/24/28 | ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1950/3120/3640 |
| WFR-19 | D:19" H:4.5" | 15/24/35 | ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1950/3120/4550 |

Options

- EMG - Emergency
- OS - Occupancy Sensor
- OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us!

info@asllighting.com