



ADA Compliant

Properties

| | |
|-------------------|----------------|
| Base Construction | Steel |
| Lens | Acrylic |
| Application | Sconce |
| Location | Damp |
| CRI | 80 |
| Life Hours | 50,000 |
| Light Source | Integrated LED |

Standard Selection

| | |
|---------|--------------------|
| Voltage | 120V Triac dimming |
| Finish | Brushed Nickel |
| CCT | 3000K |

Finish Options

☒ Brushed Nickel

CCT Options

| | |
|-----|-------------------------|
| CCT | 2700K/3000K/3500k/4000K |
|-----|-------------------------|

Options

| Size | Dimensions | Wattage | Voltage | Lumens |
|--------|----------------------|----------|--|----------------|
| WQT-11 | H:5.5" W:11" E:3.8" | 10/15 | ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) | 1300/1950 |
| WQT-15 | H:6.87" W:15" E:3.8" | 10/15 | ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) | 1300/1950 |
| WQT-19 | H:9.75" W:19" E:3.8" | 15/20/25 | ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1950/2600/3250 |

Options

OS - Occupancy Sensor

Not seeing what you're looking for?

Contact us!

info@asllighting.com