



**Properties**

<b>Base Construction</b>	Steel
<b>Lens</b>	Acrylic
<b>Application</b>	Sconce
<b>Location</b>	Damp
<b>CRI</b>	80
<b>Life Hours</b>	50,000
<b>Light Source</b>	Integrated LED

**Standard Selection**

<b>Voltage</b>	120V Triac dimming
<b>Finish</b>	Brushed Nickel
<b>CCT</b>	3000K

**Finish Options**

■ Brushed Nickel

**CCT Options**

<b>CCT</b>	2700K/3000K/3500k/4000K
------------	-------------------------

**Options**

Size	Dimensions	Wattage	Voltage	Lumens
WQT-11	H:5.5" W:11" E:3.8"	10/15	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming))	1300/1950
WQT-15	H:6.87" W:15" E:3.8"	10/15	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming))	1300/1950
WQT-19	H:9.75" W:19" E:3.8"	15/20/25	ND (120V (non dimming)) / TD (120V Triac dimming) DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/2600/3250

**Options**

OS - Occupancy Sensor

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)