# HST14

Flush Mount



BAA / CSA

## Properties

| | |
|---|---|
| Base Construction | Steel |
| Lens | Acrylic |
| Application | Flush Mount |
| Location | Damp |
| CRI | 80 |
| Life Hours | 50,000 |
| Light Source | Integrated LED |

## Standard Selection

| | |
|---|---|
| Voltage | 120V |
| Finish | Black |
| CCT | 5CCT - 2700K / 3000K / 3500K / 4000K / 5000K |

## Finish Options

- ☐ Black
- ☐ Bronze
- ☐ Gold/Brass
- ☐ ORB
- ☐ White
- ☐ Satin Nickel

## CCT Options

| | |
|---|---|
| CCT | 5CCT - 2700K / 3000K / 3500K / 4000K / 5000K |

## Options

| Size | Dimensions | Wattage | Voltage | Lumens |
|---|---|---|---|---|
| HST-11 | L:11.5" W:11.5" H:3.75" | 10/15 | 120V / ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming ) | 1300/1950 |
| HST-14 | L:14.25" W:14.25" H:4" | 15/25 | 120V / ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming ) | 1950/3250 |
| HST-19 | L:19.25" W:19.25" H:5" | 15/25 | 120V / ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming ) | 1950/3250 |

## Options

EMG - Emergency
OS - Occupancy Sensor
OSCD - Occupancy Sensor Step Dimming

**Not seeing what you're looking for?**

Contact us!

info@asllighting.com

© Copyright © 2026 ASL Lighting Inc. All rights reserved. • asllighting.com