HST19

Flush Mount



BAA / CSA

Properties

Base Construction	Steel
Lens	Acrylic
Application	Flush Mount
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED

Standard Selection

Voltage	120V
Finish	Black
CCT	5CCT - 2700K / 3000K / 3500K / 4000K / 5000K

Finish Options

- ☐ Black
- ☐ Bronze
- ☐ Gold/Brass
- ☐ ORB
- ☐ White
- ☐ Satin Nickel

CCT Options

CCT	5CCT - 2700K / 3000K / 3500K / 4000K / 5000K

Options

Size	Dimensions	Wattage	Voltage	Lumens
HST-11	L:11.5" W:11.5" H:3.75"	10/15	120V / ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/1950
HST-14	L:14.25" W:14.25" H:4"	15/25	120V / ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/3250
HST-19	L:19.25" W:19.25" H:5"	15/25	120V / ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/3250

Options

EMG - Emergency
OS - Occupancy Sensor
OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us!

info@asllighting.com

© Copyright © 2026 ASL Lighting Inc. All rights reserved. • asllighting.com