



Properties

Base Construction	Aluminum
Lens	Silicon
Application	Flush Mount
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED
Light Direction	300

Standard Selection

Voltage	120V-277V 0-10 dimming
Finish	White
CCT	4000K

Finish Options

- ☐ Black
 ☐ Bronze
 ☐ Brushed Nickel
- ☐ Gold/Brass
 ☐ ORB
 ☐ White

CCT Options

CCT	3000K/4000K/5000K
-----	-------------------

Options

Size	Dimensions	Wattage	Voltage	Lumens
C2116-12	L:11.8" W:11.8" H:0.7"	50	DVD (120V-277V 0-10 dimming)	6500
C2116-16	L:15.7" W:15.7" H:0.7"	60	DVD (120V-277V 0-10 dimming)	7800
C2116-20	L:19.7" W:19.7" H:0.7"	90	DVD (120V-277V 0-10 dimming)	11700
C2116-35	L:35.4" W:19.7" H:0.7"	125	DVD (120V-277V 0-10 dimming)	16250
C2116-43	L:43.3" W:25.6" H:0.7"	150	DVD (120V-277V 0-10 dimming)	19500

Not seeing what you're looking for?

Contact us!

info@asllighting.com