



Properties

Base Construction	Aluminum
Lens	Polycarbonate
Application	Flush Mount
Location	Dry
CRI	80
Life Hours	50,000
Light Source	Integrated LED

Standard Selection

Voltage	120V-277V (non dimming)
Finish	White
CCT	4000K

Finish Options

- Black
- Bronze
- Brushed Nickel
- Gold/Brass
- ORB
- White

CCT Options

CCT	3000K/4000K/5000K
-----	-------------------

Options

Size	Dimensions	Wattage	Voltage	Lumens
C2127-16	D:15.7" H:2.6"	20	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	2600
C2127-20	D:18.9" H:3.7"	25	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	3250
C2127-24	D:23.6" H:3.7"	40	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	5200
C2127-35	D:35.4" H:3.7"	90	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	11700
C2127-47	D:47.2" H:3.7"	150	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	19500

Not seeing what you're looking for?

Contact us!

info@asllighting.com