



Properties

Base Construction	Aluminum
Lens	Polycarbonate
Application	Recessed Ceiling Fixture
Location	Dry
CRI	80
Life Hours	50,000
Light Source	Integrated LED
Light Direction	120

Standard Selection

Voltage	120V-277V 0-10 dimming
Finish	White
CCT	4000K

Finish Options

- ☐ Black
 ☐ Bronze
 ☐ Brushed Nickel
- ☐ Gold/Brass
 ☐ ORB
 ☐ White

CCT Options

CCT	3000K/4000K/5000K
-----	-------------------

Options

Size	Dimensions	Wattage	Voltage	Lumens
C2128-20	D:20" H:3.7"	25/30	DVD (120V-277V 0-10 dimming)	3250/3900
C2128-25	D:24.8" H:3.7"	25/40	DVD (120V-277V 0-10 dimming)	3250/5200
C2128-37	D:36.3" H:3.7"	90	DVD (120V-277V 0-10 dimming)	11700
C2128-48	D:48" H:3.7"	150	DVD (120V-277V 0-10 dimming)	19500

Options

- EMG - Emergency
 OS - Occupancy Sensor
 OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us!

info@asllighting.com