







Properties	
Base Construction	Aluminum
Lens	Polycarbonate
Application	Flush Mount
Location	Dry
CRI	80
Life Hours	50,000
Light Source	Integrated LED
Light Direction	120
Standard Selection	
Voltage	120V-277V (non dimming)
Finish	White
CCT	4000K
Finish Options	
□ Black	□ Gold/Brass
□ Bronze	□ ORB
☐ Brushed Nickel	☐ White
<b>CCT Options</b>	
CCT	3000K/4000K/5000K

## Options

Size	Dimensions	Wattage	Voltage	Lumens
C2131-19	L:18.9" W:18.9" H:3.7"	25	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	3250
C2131-24	L:23.6" W:23.6" H:3.7"	40	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	5200
C2131-35	L:35.4" W:35.4" H:3.7"	90	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	11700
C2131-47	L:47.2" W:47.2" H:3.7"	180	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	23400

Not seeing what you're looking for?

Contact us!

info@asllighting.com