



Properties

| | |
|-------------------|----------------|
| Base Construction | Aluminum |
| Lens | Polycarbonate |
| Application | Flush Mount |
| Location | Dry |
| CRI | 80 |
| Life Hours | 50,000 |
| Light Source | Integrated LED |
| Light Direction | 120 |

Standard Selection

| | |
|---------|-------------------------|
| Voltage | 120V-277V (non dimming) |
| Finish | White |
| CCT | 4000K |

Finish Options

- Black
- Bronze
- Brushed Nickel
- Gold/Brass
- ORB
- White

CCT Options

| | |
|-----|-------------------|
| CCT | 3000K/4000K/5000K |
|-----|-------------------|

Options

| Size | Dimensions | Wattage | Voltage | Lumens |
|----------|---------------------------|---------|---|--------|
| C2131-24 | W:23.6" H:3.7" L:23.6" | 40 | ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 5200 |
| C2131-35 | W:35.4" H:3.7" L:35.4" | 90 | ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 11700 |
| C2131-47 | W:47.2" H:3.7" L:47.2" | 180 | ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 23400 |

Not seeing what you're looking for?

Contact us!

info@asllighting.com