



Properties

Base Construction	Aluminum
Lens	Polycarbonate
Application	Flush Mount
Location	Dry
CRI	80
Life Hours	50,000
Light Source	Integrated LED
Light Direction	120

Standard Selection

Voltage	120V-277V (non dimming)
Finish	White
CCT	4000K

Finish Options

- Black
- Bronze
- Brushed Nickel
- Gold/Brass
- ORB
- White

CCT Options

CCT	3000K/4000K/5000K
-----	-------------------

Options

Size	Dimensions	Wattage	Voltage	Lumens
C2131-19	W:18.9" H:3.7" L:18.9"	25	DV (120V-277V (non dimming)) / ND (120V (non dimming)) / TD (120V Triac dimming) / DVD (120V-277V 0-10 dimming)	3250
C2131-24	W:23.6" H:3.7" L:23.6"	40	DV (120V-277V (non dimming)) / ND (120V (non dimming)) / TD (120V Triac dimming) / DVD (120V-277V 0-10 dimming)	5200
C2131-35	W:35.4" H:3.7" L:35.4"	90	DV (120V-277V (non dimming)) / ND (120V (non dimming)) / TD (120V Triac dimming) / DVD (120V-277V 0-10 dimming)	11700

Not seeing what you're looking for?

Contact us!

info@asllighting.com