



Properties

Base Construction	Cold-rolled Steel
Lens	Acrylic
Application	Flush Mount
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED

Standard Selection

Voltage	120V-277V (non dimming)
Finish	Black/Gold
CCT	3000K

Finish Options

<input type="checkbox"/> Black	<input type="checkbox"/> ORB
<input type="checkbox"/> Bronze	<input type="checkbox"/> White
<input type="checkbox"/> Brushed Nickel	<input type="checkbox"/> Black/Gold
<input type="checkbox"/> Gold/Brass	

CCT Options

CCT	2700K/3000K/3500K/4000K/5000K
-----	-------------------------------

Options

Size	Dimensions	Wattage	Voltage	Lumens
C2134A-18	D:18" H:4"	15/24/34	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/3120/4420
C2134A-24	D:24" H:4"	25/35/48	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	3250/4550/6240

Options

EMG - Emergency
 OS - Occupancy Sensor
 OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us!

info@asllighting.com