



## Properties

|                   |                   |
|-------------------|-------------------|
| Base Construction | Cold-rolled Steel |
| Lens              | Acrylic           |
| Application       | Flush Mount       |
| Location          | Damp              |
| CRI               | 80                |
| Life Hours        | 50,000            |
| Light Source      | Integrated LED    |

## Standard Selection

|         |                         |
|---------|-------------------------|
| Voltage | 120V-277V (non dimming) |
| Finish  | Black/Gold              |
| CCT     | 3000K                   |

## Finish Options

- ☐ Black
 ☐ Bronze
 ☐ Brushed Nickel
 ☐ Gold/Brass
- ☐ ORB
 ☐ White
 ☐ Black/Gold

## CCT Options

|     |                               |
|-----|-------------------------------|
| CCT | 2700K/3000K/3500k/4000K/5000K |
|-----|-------------------------------|

## Options

| Size      | Dimensions | Wattage  | Voltage                                                                                                           | Lumens         |
|-----------|------------|----------|-------------------------------------------------------------------------------------------------------------------|----------------|
| C2134A-18 | D:18" H:4" | 15/24/34 | ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming ) | 1950/3120/4420 |
| C2134A-24 | D:24" H:4" | 25/35/48 | ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming ) | 3250/4550/6240 |

## Options

- EMG - Emergency  
 OS - Occupancy Sensor  
 OSCD - Occupancy Sensor Step Dimming

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)