



Properties

Base Construction	Aluminum
Lens	Acrylic
Application	Flush Mount
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED
Light Direction	160

Standard Selection

Voltage	120V-277V 0-10 dimming
Finish	Black
CCT	3CCT - 3000K / 3500K / 4000K

Finish Options

- | | |
|---|-------------------------------------|
| <input type="checkbox"/> Black | <input type="checkbox"/> Gold/Brass |
| <input type="checkbox"/> Bronze | <input type="checkbox"/> ORB |
| <input type="checkbox"/> Brushed Nickel | <input type="checkbox"/> White |

CCT Options

CCT	3CCT - 3000K / 3500K / 4000K
-----	------------------------------

Options

Size	Dimensions	Wattage	Voltage	Lumens
C2140-14	L:14.2" W:14.2" H:4.6"	15	DVD (120V-277V 0-10 dimming)	1950
C2140-17	L:17.7" W:17.7" H:4.6"	25	DVD (120V-277V 0-10 dimming)	3250
C2140-24	L:23.6" W:23.6" H:4.6"	36	DVD (120V-277V 0-10 dimming)	4680
C2140-32	L:31.5" W:31.5" H:4.6"	50	DVD (120V-277V 0-10 dimming)	6500

Options

EMG - Emergency

Not seeing what you're looking for?

Contact us!

info@asllighting.com