



### Properties

Base Construction	Cold-rolled Steel
Lens	Acrylic
Application	Flush Mount
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED

### Standard Selection

Voltage	120V-277V (non dimming)
Finish	Black/Gold
CCT	4000K

### Finish Options

- |   |                                     |
|---|-------------------------------------|
| <input type="checkbox"/> Black          | <input type="checkbox"/> ORB        |
| <input type="checkbox"/> Bronze         | <input type="checkbox"/> White      |
| <input type="checkbox"/> Brushed Nickel | <input type="checkbox"/> Black/Gold |
| <input type="checkbox"/> Gold/Brass     |                                     |

### CCT Options

CCT	4000K
-----	-------

### Options

Size	Dimensions	Wattage	Voltage	Lumens
C2334-15	D:14.5" H:4"	12/17/25	DV (120V-277V (non dimming)) / ND (120V (non dimming)) / TD (120V Triac dimming ) / DVD (120V-277V 0-10 dimming )	1560/2210/3250
C2334-18	D:17.5" H:4"	15/24/35	DV (120V-277V (non dimming)) / ND (120V (non dimming)) / TD (120V Triac dimming ) / DVD (120V-277V 0-10 dimming )	1950/3120/4550

### Options

EMG - Emergency  
OS - Occupancy Sensor  
OSCD - Occupancy Sensor Step Dimming

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)