EOI

Flush Mount

Properties

Base Construction	Cold-rolled Steel
Lens	Acrylic
Application	Flush Mount
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED

Standard Selection

Voltage	120V Triac dimming
Finish	Brushed Nickel
CCT	3000K

Finish Options

- ☐ Brushed Nickel

CCT Options

CCT 2700K/3000K/3500k/4000K/5000K/3CCT - 3000K / 3500K / 4000K/5CCT -

Options

Size	Dimensions	Wattage	Voltage	Lumens
EOI-15	D:15" H:3.8"	15/23/30	TD (120V Triac dimming) / DV (120V-277V (non dimming)) / ND (120V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/2990/3900
EOI-16	D:16.6" H:4.1"	15/20/28	TD (120V Triac dimming) / DV (120V-277V (non dimming)) / ND (120V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/2600/3640
EOI-18	D:18.4" H:4.1"	15/25/35	TD (120V Triac dimming) / DV (120V-277V (non dimming)) / ND (120V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/3250/4550

Options

OS - Occupancy Sensor
OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?
Contact us!
info@asllighting.com

© Copyright © 2026 ASL Lighting Inc. All rights reserved. • asllighting.com