



## Properties

Base Construction	Steel
Lens	Acrylic
Application	Flush Mount
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED

## Standard Selection

Voltage	120V Triac dimming
Finish	White
CCT	4000K

## Finish Options

<input type="checkbox"/> Black	<input type="checkbox"/> Gold/Brass
<input type="checkbox"/> Bronze	<input type="checkbox"/> ORB
<input type="checkbox"/> Brushed Nickel	<input type="checkbox"/> White

## CCT Options

CCT 2700K/3000K/4000K/5000K/3CCT - 3000K / 3500K / 4000K/5CCT - 2700K

## Options

Size	Dimensions	Wattage	Voltage	Lumens
HCD-11	D:10.87" H:3.87"	13/22	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1690/2860
HCD-14	D:14" H:4.25"	13/22	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1690/2860

## Options

OS - Occupancy Sensor  
OSCD - Occupancy Sensor Step Dimming

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)