



Properties

Base Construction	Cold-rolled Steel
Lens	Acrylic
Application	Flush Mount
Location	Dry
CRI	80
Life Hours	50,000
Light Source	Integrated LED

Standard Selection

Voltage	120V-277V (non dimming)
Finish	Brushed Nickel
CCT	3000K

Finish Options

- ☐ Black
 ☐ Bronze
 ☐ Brushed Nickel
- ☐ Gold/Brass
 ☐ ORB
 ☐ White

CCT Options

CCT 2700K/3000K/5000K/3CCT - 3000K / 3500K / 4000K/5CCT - 2700K / 3000K

Options

Size	Dimensions	Wattage	Voltage	Lumens
HCLT-15	L:15.3" W:15.3" H:4.3"	12/18/25	ND (120V (non dimming)) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1560/2340/3250
HCLT-19	L:19.3" W:19.3" H:3.8"	15/25/35	ND (120V (non dimming)) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/3250/4550

Options

- BBX-Backbox W
- ¾" Conduit hole
- EMG - Emergency
- OS - Occupancy Sensor
- OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us!

info@asllighting.com