





Properties	
Base Construction	Cold-rolled Steel
Lens	Acrylic
Application	Flush Mount
Location	Dry
CRI	80
Life Hours	50,000
Light Source	Integrated LED
Standard Selection	
Voltage	120V-277V (non dimming)
Finish	Brushed Nickel
ССТ	3000K
Finish Options	
Black	☐ Gold/Brass
Bronze	□ ORB
☐ Brushed Nickel	☐ White
CCT Options	
CCT 2700K/3000K/5000K/	3CCT - 3000K / 3500K / 4000K/5CCT - 270

## Options

Size	Dimensions	Wattage	Voltage	Lumens
HDE-15	D:14.8" H:4.6"	15/23/30	ND (120V (non dimming)) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	1950/2990/3900
HDE-18	D:17.8" H:4.8"	15/25/35	ND (120V (non dimming)) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	1950/3250/4550

**Options** 

EMG - Emergency
OS - Occupancy Sensor
OSCD - Occupancy Sensor

OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us!

info@asllighting.com