



## Properties

|                   |                |
|-------------------|----------------|
| Base Construction | Steel          |
| Lens              | Acrylic        |
| Application       | Flush Mount    |
| Location          | Damp           |
| CRI               | 80             |
| Life Hours        | 50,000         |
| Light Source      | Integrated LED |

## Standard Selection

|         |                         |
|---------|-------------------------|
| Voltage | 120V-277V (non dimming) |
| Finish  | Brushed Nickel          |
| CCT     | 4000K                   |

## Finish Options

- |                                         |                                     |
|-----------------------------------------|-------------------------------------|
| <input type="checkbox"/> Black          | <input type="checkbox"/> Gold/Brass |
| <input type="checkbox"/> Bronze         | <input type="checkbox"/> ORB        |
| <input type="checkbox"/> Brushed Nickel | <input type="checkbox"/> White      |

## CCT Options

|     |                               |
|-----|-------------------------------|
| CCT | 2700K/3000K/3500K/4000K/5000K |
|-----|-------------------------------|

## Options

| Size   | Dimensions           | Wattage     | Voltage                                                                                                           | Lumens              |
|--------|----------------------|-------------|-------------------------------------------------------------------------------------------------------------------|---------------------|
| HDT-10 | D:10" H:2.3"         | 10/15/20    | ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming ) | 1300/1950/2600      |
| HDT-12 | D:12" H:2.3"         | 10/15/20/25 | ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming ) | 1300/1950/2600/3250 |
| HDT-14 | D:14" H:2.3"         | 15/20/25    | ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming ) | 1950/2600/3250      |
| HDT-16 | D:16" H:2.3"         | 15/25/30    | ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming ) | 1950/3250/3900      |
| HDT-18 | D:18" H:2.3"         | 20/25/30    | ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming ) | 2600/3250/3900      |
| HDT-20 | D:20" H:5"           | 20/30/40    | ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming ) | 2600/3900/5200      |
| HDT-24 | D:24" H:5"           | 25/30/40    | ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming ) | 3250/3900/5200      |
| HDT-28 | L:28.3" W:14" H:4.4" | 35          | ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming ) | 4550                |

| Size   | Dimensions              | Wattage | Voltage                                                                                                           | Lumens |
|--------|-------------------------|---------|-------------------------------------------------------------------------------------------------------------------|--------|
| HDT-32 | L:32.3" W:18"<br>H:4.4" | 46      | ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming ) | 5980   |

### Options

BBX-Backbox W

¾" Conduit hole

OS - Occupancy Sensor

OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)