



Properties

Base Construction	Steel
Lens	Acrylic
Application	Flush Mount
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED

Standard Selection

Voltage	120V-277V 0-10 dimming
Finish	Brushed Nickel
CCT	3000K

Finish Options

- ☐ Black
 ☐ Bronze
 ☐ Brushed Nickel
- ☐ Gold/Brass
 ☐ ORB
 ☐ White

CCT Options

CCT	3000K
-----	-------

Options

Size	Dimensions	Wattage	Voltage	Lumens
HDTE-12	D:12" H:4.25"	14	DVD (120V-277V 0-10 dimming) / DV (120V-277V (non dimming))	1820
HDTE-14	D:14" H:4.43"	18	DVD (120V-277V 0-10 dimming) / DV (120V-277V (non dimming))	2340
HDTE-16	D:16" H:5.52"	24	DVD (120V-277V 0-10 dimming) / DV (120V-277V (non dimming))	3120
HDTE-18	D:17.7" H:5.9"	35	DVD (120V-277V 0-10 dimming) / DV (120V-277V (non dimming))	4550

Options

OS - Occupancy Sensor
OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us!

info@asllighting.com