



### Properties

|                   |                |
|-------------------|----------------|
| Base Construction | Steel          |
| Lens              | Acrylic        |
| Application       | Flush Mount    |
| Location          | Damp           |
| CRI               | 80             |
| Life Hours        | 50,000         |
| Light Source      | Integrated LED |
| Light Direction   | 120            |

### Standard Selection

|         |                              |
|---------|------------------------------|
| Voltage | 120V Triac dimming           |
| Finish  | Black/Gold                   |
| CCT     | 3CCT - 3000K / 3500K / 4000K |

### Finish Options

- ☐ Black
 ☐ ORB
- ☐ Bronze
 ☐ White
- ☐ Brushed Nickel
 ☐ Black/Gold
- ☐ Gold/Brass

### CCT Options

CCT 3CCT - 3000K / 3500K / 4000K/5CCT - 2700K / 3000K / 3500K / 4000K / 5

### Options

| Size     | Dimensions          | Wattage  | Voltage                                            | Lumens         |
|----------|---------------------|----------|----------------------------------------------------|----------------|
| HOSTB-13 | L:13" W:13"<br>H:4" | 15/20/25 | ND (120V (non dimming)) / TD (120V Triac dimming ) | 1950/2600/3250 |

### Options

BBX-Backbox W  
 ¾" Conduit hole  
 EMG - Emergency  
 OS - Occupancy Sensor  
 OSCD - Occupancy Sensor Step Dimming

**Not seeing what you're looking for?**

Contact us!

[info@asllighting.com](mailto:info@asllighting.com)