







Properties	
Base Construction	Steel
Lens	Acrylic
Application	Flush Mount
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED

Standard Selection

Voltage	120V Triac dimming
Finish	White
CCT	3000K

Finish Options	
□ Black	☐ Gold/Brass
□ Bronze	□ ORB
☐ Brushed Nickel	☐ White
CCT Options	
CCT	2700K/3000K/3500k/4000K/5000K

Options

Size	Dimensions	Wattage	Voltage	Lumens
HSA-11	D:11" H:3.5"	13/22	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1690/2860
HSA-14	D:15" H:3.8"	13/22	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1690/2860
HSA-19	D:19" H:3.8"	15/25	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/3250

Options

EMG - Emergency
OS - Occupancy Sensor
OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us!

info@asllighting.com