







Base Construction	Steel				
Lens	Acrylic				
Application	Flush Mount				
Location	Damp				
CRI	80				
Life Hours	50,000				
Light Source	Integrated LED				
Standard Selection					
Voltage	120V Triac dimming				
Finish	Brushed Nickel				
CCT	5CCT - 2700K / 3000K / 3500K / 4000K / 5000K				
Finish Options					

☐ Gold/Brass

5CCT - 2700K / 3000K / 3500K / 4000K / 5000K

 \square ORB

□ White

Options

Size	Dimensions	Wattage	Voltage	Lumens
HST-11	L:11.5" W:11.5" H:3.75"	10/15	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1300/1950
HST-14	L:14.25" W:14.25" H:4"	15/25	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/3250
HST-19	L:19.25" W:19.25" H:5"	15/25	ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming)	1950/3250

Properties

□ Black

CCT

□ Bronze

☐ Brushed Nickel

CCT Options

Options

OS - Occupancy Sensor
OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us! info@asllighting.com