



Properties

| | |
|-------------------|----------------|
| Base Construction | Steel |
| Lens | Acrylic |
| Application | Flush Mount |
| Location | Damp |
| CRI | 80 |
| Life Hours | 50,000 |
| Light Source | Integrated LED |

Standard Selection

| | |
|---------|--|
| Voltage | 120V Triac dimming |
| Finish | Brushed Nickel |
| CCT | 5CCT - 2700K / 3000K / 3500K / 4000K / 5000K |

Finish Options

- Black
- Bronze
- Brushed Nickel
- Gold/Brass
- ORB
- White

CCT Options

| | |
|-----|--|
| CCT | 5CCT - 2700K / 3000K / 3500K / 4000K / 5000K |
|-----|--|

Options

| Size | Dimensions | Wattage | Voltage | Lumens |
|--------|-------------------------------|---------|---|-----------|
| HST-11 | W:11.5" H:3.75" L:11.5" | 10/15 | ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1300/1950 |
| HST-19 | W:19.25" H:5" L:19.25" | 15/25 | ND (120V (non dimming)) / TD (120V Triac dimming) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming) | 1950/3250 |

Options

- EMG - Emergency
- OS - Occupancy Sensor
- OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

Contact us!

info@asllighting.com