







## **Properties**

Base Constru	ction Steel
Lens	Acrylic
Application	Flush Mount
Location	Damp
CRI	80
Life Hours	50,000
Light Source	Integrated LED

## **Standard Selection**

Voltage	120V Triac dimming
Finish	Brushed Nickel
CCT	5CCT - 2700K / 3000K / 3500K / 4000K / 5000K

Finish Options				
□ Black	□ Gold/Brass			
□ Bronze	□ ORB			
☐ Brushed Nickel	□ White			
CCT Options				

## Options

Size	Dimensions	Wattage	Voltage	Lumens
HSTB-8	L:8" W:8" H:3"	10/15	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	1300/1950
HSTB-10	L:10" W:10" H:3"	10/15	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	1300/1950
HSTB-12	L:12" W:12" H:3.25"	15/25	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	1950/3250
HSTB-14	L:14" W:14" H:4"	15/25	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	1950/3250
HSTB-19	L:19" W:19" H:4"	15/25	ND (120V (non dimming)) / TD (120V Triac dimming ) / DV (120V-277V (non dimming)) / DVD (120V-277V 0-10 dimming )	1950/3250

CCT

## **Options**

EMG - Emergency
OS - Occupancy Sensor
OSCD - Occupancy Sensor Step Dimming

Not seeing what you're looking for?

5CCT - 2700K / 3000K / 3500K / 4000K / 5000K

Contact us! info@asllighting.com